

Practice would have been too extensive, and thus would have been too  
burdensome. The present amendment is intended for clarification purposes only  
and not for substantial reasons related to patentability pursuant to 35 U.S.C. §§103,  
102, 103 or 112. Indeed, the cancellation of claims 1-12 does not constitute an  
5 intent on the part of the Applicant to surrender any of the subject matter of claims  
1-12.

Early consideration on the merits is respectfully requested.


Respectfully submitted,

10

BELL, BOYD & LLOYD LLC

15

BY

  
\_\_\_\_\_  
William E. Vaughan  
Reg. No. 39,036  
P.O. Box 1135  
Chicago, Illinois 60690-1135  
Phone: (312) 807-4292

VERSION WITH MARKINGS TO SHOW CHANGES MADE

~~Description~~

~~Method for conveying information between a switching office and a  
communications terminal~~

5

SPECIFICATION

TITLE OF THE INVENTION

METHOD AND TELECOMMUNICATIONS NETWORK FOR CONVEYING  
INFORMATION BETWEEN A SWITCHING OFFICE AND A  
COMMUNICATIONS TERMINAL

10

BACKGROUND OF THE INVENTION

The present invention ~~also~~ relates to a method for transmitting data to operators of a telecommunications network which are members of an operator service, the data being specifically for the operator service, and at least one data channel and at least one call channel being available for each link.

15

The present invention also relates to a telecommunications network having a plurality number of switching offices, in which telecommunications network operators which are members of an operator service are connected to at least one switching office, and each switching office has at least one coordination processor and peripheral line trunk groups with a group processor for the subscribers.

20

What are referred to as operator services which constitute an essential link between the customers of the network and the network operators are required in telephone networks. Such an operator service has diverse functions, one main function being to distribute information to subscribers on request. For example, a subscriber may call an operator service in an ISDN network and request  
25 information. The respective operator can then, if necessary, access a database, for example, in which case information relating to another subscriber is then provided to him/her on the screen of a PC. After a connection request by the operator, which can be effected, for example, by pressing a push-button key, the operator is connected to the searched-for subscriber. The operator is then connected back to  
30 the originating subscriber and to the searched-for subscriber and can optionally speak to one of the subscribers. Signaling on the D channel then takes place again

at the push of a further push-button key, and the connection situations of the two subscribers of the peripheral line trunk group are indicated, and the call channels are connected via the switching matrix so that ultimately there is a direct link between the two subscribers. The example described here is intended to represent  
5 just one of the possibilities or functions of an operator service.

Larger networks with a larger number of subscribers require a correspondingly large number of operator service systems with a large number of usually hierarchically structured system subscribers (operators), such as, for example, as in the case of the Applicant's system which is called ADMOSS.  
10 Messages from the operators to a switching office are sent, as already mentioned, in the D channel in an ISDN network, specifically in a point-to-point configuration with a permanently active layer 2 of the OSI layer model. The messages are transmitted in an ISDN network with the support of the D channel protocol, for which reason reference is also made to the Blue Book, Volume VI - Fascicle VI.  
15 11, "Digital Subscribe Signalling System No. 1 (DSS1), Network Layer, User-Network Management", Recommendations Q. 930 - Q. 940, in particular to Recommendation Q. 931.

The operators are usually located in what are referred to as call centers, and a respective device, composed of a terminal, PC, screen etc., and referred to below;  
20 ~~as is the usual practice,~~ as "console" is directly connected to the system and/or can be connected to the local switching office. However, the need to use decentralized operators, for example within the context of homeworkers, is being increasingly felt, but a single central management system for the operators in the network should still be possible.

25 The PC of each operator has software installed which is suitable for the operator service, but when the operator logs on, i.e. the console is respectively first put into operation, data from the carrier is also required. In such a case, the operator logs on by inputting his/her password and ~~his~~ ID numbers and specific data is then loaded onto the console ("downloading") by the carrier, this data being, for  
30 example, the system clock times and data, the hierarchy structure, personal data and different rights, for example access possibilities to statistical data etc. If the

operator is a supervisor, i.e. a high-ranking member in the hierarchy, he/she will also obtain access to tables which provide information on the working status of other operators etc.

5 ~~One object of the invention is to disclose a method which permits the  
aforesaid specific information, which will be available in a centrally stored form, to  
be loaded to operator consoles which may be situated at any desired location in a  
network, without complex changes to existing systems being required.~~

US-A-5,469,504 describes a call distributor system having a host computer together with a database which is physically connected to all the switching offices,  
10 and serves as a system for switching and/or conveying the data between the individual switching offices to which operators of an operator service are connected. In this system, a call link is firstly offered to an operator via the local switching office and, if the operator is not suitably located for this call, this call is transferred to a further operator using the host computer, this transfer being made  
15 using a special protocol, referred to in the document as "intertandem protocol". This protocol uses a DTMF method. The expenditure incurred as a result of the use of the host computer in conjunction with the X.25 interface protocol described in the document and the intertandem protocol is, however, to be considered as disadvantageous.

20 One object of the present invention is to disclose a method which permits the aforesaid specific information, which will be available in a centrally stored form, to be loaded to operator consoles which may be situated at any desired location in a network, without complex changes to existing systems being required.

#### SUMMARY OF THE INVENTION

25 This object is achieved with a method ~~of the type mentioned at the beginning~~ in which, according to the present invention, after an operator logs ~~onto~~ on to a remote master office in which the specific data for the operator service are present centrally, a request is transmitted by the coordination processor of the master office to a virtual operator set up in a peripheral line trunk group in order to  
30 initiate a dialing process to the operator, after which a link setup to the subscriber is carried out via a call channel and a corresponding message is transmitted to the

coordination processor, ~~the~~ . The data to be transmitted are then loaded in the master office from the coordination processor into a group processor, a data transmission link in the master office is set up starting from this group processor to a peripheral line trunk group for fast data links, and the data to be transmitted is then transmitted via a data link to a peripheral line trunk group for fast data links between the switching office of the operator and from there, within the switching office, to the peripheral line trunk group (LTG) of the operator, ~~and finally~~ . Finally, the data to be transmitted is transmitted from this peripheral line trunk group to the operator (OP1).

~~Thanks~~ Pursuant to the present invention, operators which are also connected to different switching offices of a communications network can receive specific, centrally managed data, this loading of data not necessarily having to be restricted to the initialization phase when logging on is performed.

It is expedient if the data to be transmitted is transmitted from the peripheral line trunk group to the operator via a data channel, this constituting the customary possibility for the data transmission, which also should be provided in the network in accordance with regulations.

However, because, ~~on the other hand~~, a call connection is set up according to the present invention, it ~~may~~ also may be appropriate if the data to be transmitted is transmitted via the set-up call channel using a data link program.

In order to take into account the dynamics and the resources of the group processor of the master office, an indication is given if the data from the coordination processor of the master office is loaded into the group processor in blocks of limited size via an existing data link interface.

The present invention is particularly suitable for applications in an ISDN network, the data channel being the D channel, and the call channels being B channels. In this case, the inter-office signaling system is advantageously an ISUP signaling system.

The aforementioned object of the present invention is also achieved with a telecommunications network ~~of the type specified at the beginning~~, in which, according to the present invention, a virtual operator is set up in a peripheral line

trunk group of a switching office serving as master office, and is provided for transmitting data from the coordination processor of the master office to an operator of the operator service, ~~and the~~ . The coordination processor of the master office is configured to transmit a request to the virtual operator, and to initiate a dialing process to the operator so that the data to be transmitted can be transmitted, after setting up of a data transmission link within the master office, via a peripheral line trunk group for fast data links of the master office to such a line trunk group of the switching office of the operator and can be transmitted from this switching office to the operator.

Additional features and advantages of the present invention are described in, and will be apparent from, the following Detailed Description of the Invention and the Figures.

#### BRIEF DESCRIPTION OF THE FIGURES

Figure 1 shows the basic structure of a network with two switching offices and an operator service.

#### DETAILED DESCRIPTION OF THE INVENTION

~~The advantages which can be achieved in this way and those which are related to the features of the dependent claims 8 to 12 correspond to the advantages mentioned in conjunction with the method and the invention.~~

~~The invention, together with further advantages, is explained in more detail below with reference to an exemplary embodiment and by means of the drawing. The latter shows in its single figure the basic structure of a network with two switching offices illustrated and an operator service.~~

#### DETAILED DESCRIPTION OF THE INVENTION

At the top left of the figure there are a number of operators OP1, OP2 ... of an operator service OPS, details of the hierarchy within the operators OP1, OP2 ... not being given here. All operators OP1, OP2 ... are next to customary network operators TEI of a telecommunications network NET, of an ISDN network in the present case, and are therefore connected into the network via an S<sub>0</sub> interface; i.e., each connected here to a network terminal NTE.

A first switching office VS1 of the network is shown top right and it has, in a manner known per se, a switching matrix SNE and periphery line trunk groups LTG, LTC connected thereto. A coordination processor COP is provided for controlling the switching office VS1, especially the switching matrix SNE. Each peripheral line trunk group LTG, LTC also contains, in a known manner, a group processor GRP, and in . In this exemplary embodiment concentrators DLU (Digital Line Unit) are connected to each peripheral line trunk group via a  $U_{k0}$  interface. Each of these concentrators DLU also has a plurality number of inputs for the network terminals already mentioned above. In the case of relatively large switching offices, up to 512 peripheral line trunk groups LTG, LTC can be connected to a switching matrix SNE, and usually two concentrators DLU are connected to each line trunk group LTG. The peripheral line trunk groups LTG, LTC each also contain, in a known manner, what is referred to as a group switch GSI.

In a peripheral line trunk group LTG, LTC, various programs are executed which are supported by the group processor GRP; for example, the greater part of the connection setup, the signaling, the code reception etc., takes place here. In general, 70% of the connection setup is carried out in the peripheral line trunk groups, whereas especially routing functions are assigned to the coordination processor COP.

The switching office also ~~comprises~~ includes an operation and maintenance system OMS with an operation and maintenance terminal OMT at which monitoring personnel can continuously monitor the state of the switching office and detect faults.

The operators OP1, OP2 ... of the operator service OPS usually have workstations with personal computers which contain ISDN cards and special software as well as headsets for the operators. The operators OP1, OP2, ... can transmit messages to the switching office, especially to the peripheral line trunk groups LTG, these messages being processed in the group processor GRP and devised to corresponding further measures; for example, a connection setup. The

messages are transmitted in a point-to-point configuration with a permanently active layer 2 and in the D channel in an ISDN network.

Bottom right in the drawing there is a further switching office VS2 which is associated with the network NET and whose setup corresponds basically to the first switching office VS1, but the second switching office VS2 serves as a master office above the operator service. Of course, a large number of other switching offices (not shown here) may also may be provided as a function of the size of the network.

Each switching office VS1, VS2 has a particular peripheral line trunk group LTC for fast data links which permit data exchange, within the scope of inter-office signaling; for example, in the ISUP signaling system (see, for example, P. Bocker, ISDN - Digitale Netze für Sprach-, Text-, Daten-, Video- und Multimediakommunikation [Digital Networks for Call, Text, Data, Video and Multimedia Communication], 4th Edition, Springer [Publishing house], Section 6.2.9, "Zwischenamtsignalisierung" [Inter-office signaling]), with other such line trunk groups via rapid data links, for example optical fiber lines.

In the present case, that data which is to be loaded into the consoles of the operators OP1, OP2, ... may be in the remote office, i.e. the switching office VS2, namely in its coordination processor COP. In order to transmit the aforesaid data which is specifically for the operator service and which is composed, for example, of tables for the function of the console, to the operator OP1, the present invention provides a method described in more detail below.

Firstly, the operator OP1 logs on with a password and an ID number to the remote switching office VS2, the master office, which is, however, not a subject of the present invention. In principle, after the operator OP1 logs ~~onto~~ on to the remote switching office VS2, the coordination processor COP of the master office VS2 transmits a request to a virtual operator VOP to initiate a dialing process to the operator OP1. Such a virtual operator, which is set up in a peripheral line trunk group LTG, is required by the coordination processor COP in order to be able to set up a call link. In fact, a connection setup is then carried out starting from the virtual operator VOP, to the operator OP1 via a call channel, here a B channel, and after



the successful connection setup the coordination processor COP is also informed of the call status and also informed in the event of a disconnection of the link.

The corresponding program part then initiates, given a successful setup of a link, a data link connection from a PC or the like to the coordination processor, a  
5 corresponding identification of this new type of link, which ~~can~~ can be referred to as a "remote downloading" link, being used. The data is then loaded, for example, in blocks of four kbytes into a group processor GRP by the coordination processor ~~by means of~~ via the existing data link interface. A data transmission link RIN (Report Interface) in the master office VS2 is then set up  
10 starting from this group processor GRP to a peripheral line trunk group LTC. This line trunk group LTC is used for fast data links to other offices, the data to be transmitted then being transmitted via a fast data link, for example an optical fiber cable, to a corresponding peripheral line trunk group LTC of the switching office VS1 of the subscriber OP1, from here within the switching office VS1 to the  
15 peripheral line trunk group LTG of the subscriber, ~~and finally~~ Finally, the data to be transmitted are transmitted from this peripheral line trunk group LTG to the operator OP1 and loaded there. The transmission from the peripheral line trunk group LTG of the operator OP1 to the latter is made via a D channel in which a data link to the console is set up. However, it is also possible to load the further  
20 data into the console via a B channel link, for which purpose a corresponding data transmission protocol has to be employed for using the B channel as a data transport medium. After all the data has been transmitted, the data link connection is released and finally the existing call between the operator OP1 and the vertical operator is also released from the console.

25 It is to be noted that the loading of data does not necessarily have to have its starting point in a request of the operator OP1, but a link from the master office to the operator OP1 can instead also be made at the request of the operator service using the virtual operator VOP. Of course, all this presumes that the call numbers of the corresponding operators OP1, OP2, ... are known to the master office VS2.  
30 In this context, it is necessary to set up a call for addressing purposes, and the data can then, as already mentioned, ~~either~~ be transmitted either over the D channel at

16 kbit/s in the case of ISDN or even over a B channel with an even higher speed; namely, 64 kbit/s in the case of ISDN. The present invention therefore permits a significant expansion of an operator service because the latter can be integrated into a large network with a multiplicity of switching offices (only two are shown in  
5 the drawing for the sake of simplification), and nevertheless centralized and clearly organized management is possible. The data loaded into the console also makes it possible to take into account the hierarchy in the operator service which is mentioned at the start, so that higher-ranking operators can receive preferred data which is not to be made available to all operators.

10 Although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be made thereto without departing from the spirit and scope of the invention as set forth in the hereafter appended claims.

Abstract

ABSTRACT OF THE DISCLOSURE

Method for conveying information between a switching office which is arranged in  
a communications network and at least one communications terminal or subscriber  
5 which is assigned to the communications network, and use of the method and  
telecommunications network

A method and a telecommunications network (NET) for transmitting data to  
subscribers (OP1) of an operator service (OPS), in which, after a subscriber (OP1)  
10 logs ~~on to~~ on to a remote master office (VS2), a request is transmitted from his/her  
coordination processor (COP) to a virtual operator (VOP) in order to initiate a  
dialing process to the subscriber (OP1), a link setup to the subscriber is carried out  
via a voice channel, the data to be transmitted is then loaded in the master office  
from the coordination processor (CP2) into a group processor (GRP), a data  
15 transmission link (RLN) in the master office (VS2) is set up to a peripheral line  
trunk group (LTC) for fast data links, and the data to be transmitted is then  
transmitted via a data link to the switching office (VS1) of the subscriber (OP1)  
and from here to the subscriber (OP1).

20 Fig. 1